

LED-ERHVERV

v. Bjarne H. Jensen

CVR: 17500392

Erhvervsparken 7, 7800 Skive

1.5M LED Tube Light

Part No: FJ-T8-150-24W



Introduction

LED tubes are the ideal replacement for the conventional fluorescent tube, energy-saving up to 70%. Designed with advanced heat dissipation technology, used high brightness SMD LED and super internal constant current driver, The LED tubes are brighter than conventional fluorescent tube, better than most similar LED tubes in the market.

Product Features


- High Brightness: Taiwan Epistar chip, light efficiency of tube reach to 100lm/w;
- Super driver: Conversion efficiency above 93% and power factor reach to 98%;
- Thermal technology: Advanced technology with first class radiator materials;
- Modular Structure: Modular design, easy assembly and disassembly.
- Certificate: CE, approval and RoHS compliant;
- Warranty: 3 years.

Technical Specification




Part No.	FJ-T8-150-24W	
Rated Power	24-25W	
Input Voltage	AC85V-265V,50-60Hz	
LED Quantity	120PCS	
Color Temperature	2800k~3200K;4000k~4500K;5500k~6500K	
Conversion Efficiency	93%	
Power Factor	0.97	
Beam Angle	120°	
Product photo (SMD 2835)	Pin Type	G13
	Dimension	∅ 26*L1498mm
	Diffuser	Frosted PC/Clear cover
Luminous Flux	2400-2500lm	
Illuminance	1m=529lux,2m=160lux,3m=75lux	
Operate Temperature	-20°C~+50°C	
Storage Temperature	-20°C~+50°C	
Color Rendering Index	>70	
Materials	Aluminum alloy&PC	
Equal to conventional fluorescent tube	58W+8W (Ballast Power)	


illuminance:




Viewing Angle



Illuminance Maintenance



Dimension Drawing




Application

Ideal replacement for conventional fluorescent tubes, widely used for office, factory, parking lot, residential, warehouse, signage passenger interiors, supermarket, shop, vehicle interiors, etc



Installation


To avoid the danger of being shocked or electrocuted, turn off power to the fixture and unplug or detach fixture from source of power.



Package

Outer Carton: 1570*240*240mm(25pcs/box)

Gross weight: 12kg/Carton



25 pieces per Carton